



BALE NETWRAP

Karatzis S.A. **Bale Netwrap** is made of HDPE of highest quality providing maximum tensile strength and highest resistance to tearing.



APPLICATION:

- Your best choice
- State of the art machinery equipment
- Continuous quality control
- For baling hay, straw or silage
- Suitable for all balers
- Maximum bale coverage
- Perfectly wound rolls
- Continuous wrapping
- Every roll UV stabilized

BALE NETWRAP

Netzwerk premium is one of the best solutions for perfect round bale wraps (2-3 turns to make it a perfect bale). It provides you with full, consistent and uniform bale coverage while achieving a fast baling process. Our net is suitable for all crops (hay, straw, silage) under all weather conditions.

A unique quality certificate for our net in the form of an official recommendation by the DLG (German Farming Association) which we received in 1999 was renewed in August 2003 by passing the **Signum-Test**. Our net was tested on all saleable balers worldwide as well as checked for technical specifications. You will find more details in our DLG report No. 5179 (www.dlg-test.de).

In addition to Netzwerk premium we offer a wide range of bale netwrap products in order to satisfy the needs of all customers. Such products are customized in order to fit and satisfy the needs of individual customers.

- Antistatic additives added to each roll
- Guaranteed length of 2.000 m, 2.500 m and 3.000 m (5% positive tolerance included)
- Control number system to identify each roll
- Suitable for all crops under all conditions
- Good weather protection
- 2 - 3 turns to make it a perfect bale
- Red end warning on the last 50 m





SPECIFICATION			PACKAGING			
Meters/roll	Net width in cm	Core diameter in cm	Rolls/pallet	Pallets/truck	Pallets/20ft ctr	Pallets/40ft ctr
2.000	60 / 123 / 125 / 130*	76	32	22	8	18
3.000	60 / 123 / 125 / 130*	76	28	20	8	18

*Also bigger sizes available on customer request

TECHNICAL DATA				
Roll width (+10 mm)	0,60 m	1,23 m	1,25 m	1,30 m
Roll length	Available in lengths of 2.000 m, 2.500 m and 3.000 m			
Roll diameter (+10 mm)	240 mm (2.000 m) or 280 mm (3.000 m)			
Core length	625 mm	1.245 mm	1.260 mm	1.325 mm
Core internal diameter	76 mm			
Packing	Plastic film*			
Antistatic additives	Yes			
UV stabilized	Yes			

*Other types of packaging available on customer request



KARATZIS S.A. · INDUSTRIAL AREA 711 · 10 HERAKLION · P.O. BOX 1490 CRETE · GREECE
TEL. +30(2810)380901 · FAX +30(2810)381400 · E-MAIL SALES@KARATZIS.GR

MORE DETAILED INFORMATION UNDER WWW.KARATZIS.COM